



HD 6/16-4MX

Dimensions (L x W x H)	467 x 407 x 1010 mm
Power cord	-
Power rating	3,4 kW
Operating pressure	30-160/3-16 bar/MPa
Flow rate	230-600 l/h
Weight	50 kg
Max. pressure	190/19 bar/MPa
Cleaning agent tank	-
Type of current	1/230/50 Ph/V/Hz
Feed temperature	60 °C



HDS 9/18 -4M

Dimensions (L x W x H)	1330 x 750 x 1060 mm
Power cord	-
Power rating	6,4 kW
Outside temperature	-
Fuel tank	25 l
Pressure	30-180/3-18 bar/MPa
Flow rate	450-900 l/h
Weight	156 kg
Heat output	-
Fuel tank	-
Cleaning agent tank	20 l
Type of current	3/400/50 Ph/V/Hz
Tank capacity	10 l
Max. temperature (feed 12°C)	80-155 °C
Fuel oil consumption, full load	5,8 kg/h



HDS 7/16 CX

Dimensions (L x W x H)	1215 x 650 x 920 mm
Power cord	5 m
Power rating	4,7 kW
Outside temperature	-
Fuel tank	15 l
Pressure	30-160/3-16 bar/MPa
Flow rate	270-660 l/h
Weight	105 kg
Heat output	-
Fuel tank	-
Cleaning agent tank	10 l
Type of current	3/400/50 Ph/V/Hz
Tank capacity 2	-
Max. temperature (feed 12°C)	155 °C
Fuel oil consumption, full load	4,1 kg/h



HD 10/25-4S

Dimensions (L x W x H)	560 x 500 x 1090 mm
Power cord	-
Power rating	9,2 kW
Operating pressure	30-250/3-25 bar/MPa
Flow rate	500-1000 l/h
Weight	62 kg
Max. pressure	275/27,5 bar/MPa
Cleaning agent tank	6 l
Type of current	3/400/50 Ph/V/Hz
Max. feed temperature	60 °C



HD 6/15 CX EU

Dimensions (L x W x H)	360 x 400 x 925 mm
Power cord	-
Power rating	3,1 kW
Operating pressure	30-150/3-15 bar/MPa
Flow rate	230-560 l/h
Weight	28 kg
Max. pressure	190/19 bar/MPa
Cleaning agent tank	-
Type of current	1/230/50 Ph/V/Hz
Feed temperature	60 °C



HD 5/15C

Dimensions (L x W x H)	360 x 375 x 925 mm
Power cord	-
Power rating	2,7 kW
Operating pressure	30-150/3-15 bar/MPa
Flow rate	230-500 l/h
Weight	23 kg
Max. pressure	185/18,5 bar/MPa
Cleaning agent tank	0 l
Type of current	1/230/50 Ph/V/Hz
Feed temperature	60 °C



HDS 6/14 CX EU

Dimensions (L x W x H)	1215 x 650 x 920 mm
Power cord	5 m
Power rating	3,6 kW
Outside temperature	-
Fuel tank	15 l
Pressure	30-140/3-14 bar/MPa
Flow rate	240-560 l/h
Weight	95 kg
Heat output	-
Fuel tank	-
Cleaning agent tank	10 l
Type of current	1/230/50 Ph/V/Hz
Tank capacity 2	-
Max. temperature (feed 12°C)	155 °C
Fuel oil consumption, full load	3,5 kg/h



HD 728 B CAGE GB

Dimensions (L x W x H)	570 x 434 x 430 mm
Pressure	150/15 bar/MPa
Flow rate	650 l/h
Weight	28 kg
Weight without accessories	-
Max. pressure	160/16 bar/mbar
Engine manufacturer	Honda
Power rating	4/5,5 kW/PS
Engine performance, net.	3,6 kW
Engine type	GX 160/petrol
Feed temperature	60 °C



K 2.325

Dimensions (L x W x H)	280 x 242 x 623 mm
Power rating	1,4 kW
Pressure	110/11 bar/MPa
Flow rate	360 l/h
Frequency	50 Hz
Weight without accessories	4,9 kg
Power	-
Cleaning agent tank	-
Voltage	230-240 V
Feed temperature	40 °C



K 3.550 MD

Dimensions (L x W x H)	300 x 325 x 876 mm
Power rating	1,8 kW
Pressure	20-120/2-12 bar/MPa
Flow rate	420 l/h
Frequency	50 Hz
Weight without accessories	12,6 kg
Power	-
Cleaning agent tank	1 l
Voltage	230 V
Feed temperature	40 °C



K 4600 MD

Dimensions (L x W x H)	349 x 395 x 867 mm
Power rating	1,9 kW
Pressure	20-130/2-13 bar/MPa
Flow rate	440 l/h
Frequency	50 Hz
Weight without accessories	13 kg
Power	-
Cleaning agent tank	1 l
Voltage	230 V
Feed temperature	40 °C



K 5.700 MD

Dimensions (L x W x H)	349 x 426 x 878 mm
Power rating	2,1 kW
Pressure	20-140/2-14 bar/MPa
Flow rate	460 l/h
Frequency	50 Hz
Weight without accessories	14,5 kg
Power	-
Cleaning agent tank	1 l
Voltage	230 V
Feed temperature	40 °C



K 7700

Dimensions (L x W x H)	404 x 461 x 968 mm
Power rating	3 kW
Pressure	20-160/2-16 bar/MPa
Flow rate	600 l/h
Frequency	50 Hz
Weight without accessories	20 kg
Power	-
Cleaning agent tank	1 l
Voltage	230 V
Feed temperature	-



T12/1 EU

Dimensions (L x W x H)	340 x 315 x 410 mm
Number of phases	-
Power rating	1300 W
Container capacity	12 l
Frequency	50-60 Hz
Weight	6,6 kg
Cable length	12 m
Brush motor power rating	-
Turbine power rating	-
Air flow rate	61 l/s
Sound pressure level	61 dB A
Voltage	220-240 V
Standard nominal width	32 mm
Standard nominal width	-
Vacuum	244/24,4 mbar/kPa



NT 40/1 TACT EU

Dimensions (L x W x H)	555 x 380 x 870 mm
Quantity	-
Working width	-
Power rating	1380 W
Container material	Plastic
Container capacity	40 l
Fresh water container capacity	-
Waste water container capacity	-
Frequency	50-60 Hz
Weight	14,1 kg
Weight without accessories	-
Cable length	7,5 m
Brush motor power rating	-
Electric flow heater power	-
Power rating pump	-
Turbine power rating	-
Air flow rate	61 l/s
Sound pressure level	67 dB A
Voltage	220-240 V
Spray pressure	-
Spray rate	-
Standard nominal width	35 mm
Standard nominal width	-
Vacuum	230/23 mbar/kPa



NT 65/2 AP EU

Dimensions (L x W x H)	600 x 480 x 920 mm
Quantity	1 Ph
Working width	-
Power rating	2760 W
Container material	Plastic
Container capacity	65 l
Fresh water container capacity	-
Waste water container capacity	-
Frequency	50-60 Hz
Weight	20 kg
Weight without accessories	-
Cable length	10 m
Brush motor power rating	-
Electric flow heater power	-
Power rating pump	-
Turbine power rating	-
Air flow rate	74 l/s
Sound pressure level	73 dB A
Voltage	220-240 V
Spray pressure	-
Spray rate	-
Standard nominal width	40 mm
Standard nominal width	-
Vacuum	254/25,4 mbar/kPa



SDP 7000

Dimensions (L x W x H)	170 x 190 x 310 mm
Connecting thread	20 mm
Power cord	G1
Delivery head/pressure, max.	H05RN-F, 10m/11 /m
Flow rate	6/0,6 m/bar
Delivery temperature, max.	7000 l/h
Weight without accessories	35 °C
Max. grain size	4,3 kg
	20 mm

Max. depth of immersion	8 m
Power rating	320 W



SDP 14000

Dimensions (L x W x H)	220 x 220 x 390 mm
	25 mm
Connecting thread	G1 1/4
Power cord	H07RN-F, 10m/11 /m
Delivery head/pressure, max.	8/0,8 m/bar
Flow rate	14000 l/h
Delivery temperature, max.	35 °C
Weight without accessories	6,8 kg
Max. grain size	25 mm
Max. depth of immersion	8 m
Power rating	800 W



SDP 18000

Dimensions (L x W x H)	220 x 220 x 400 mm
	30 mm
Connecting thread	G1 1/4
Power cord	H07RN-F, 10m/11 /m
Delivery head/pressure, max.	9/0,9 m/bar
Flow rate	18000 l/h
Delivery temperature, max.	35 °C
Weight without accessories	8 kg
Max. grain size	30 mm
Max. depth of immersion	8 m
Power rating	1100 W